

# Aquafax



**Mechanical steering system for a boat with one outboard engine with a total of **55hp (40kW) or less****

You will need the following:

- 1 x Steering helm
- 1 x Steering cable
- 1 x Steering wheel
- 1 x Engine connection kit (optional)

See also the Aquafax range of Steering System Accessories



Aquafax Limited.  
14 Dencora Way, Sundon Business Park,  
Luton, Beds LU3 3HP  
Tel: (01582) 568700 Fax: (01582) 568720  
E-mail: sales@aquafax.co.uk  
Website: www.aquafax.co.uk

## 4-T67/W Features and Technical Information



CE

- All stainless steel output end of cable as per ABYC P17 safety standards
- Corrosion resistant materials
- Standard friction externally adjustable
- 90° bezel
- Four optional helm positions to facilitate steering cable installation
- Stroke: 230mm (9")
- Lock to lock steering wheel turns: approx 2.5
- Minimum steering cable bend radius: 200mm (7.9")
- Exceeds EN 29775 safety standards

4-T67



4-T67W



## Boat Application

Outboard applications only  
For boats with engine power of up to 40kW (55hp)

## Steering Wheel

(Max dia 380mm/15")


CE



4-VM24

Various styles of steering wheels are available, please see the full Aquafax range.


## M58 Steering Cable




- |                 |                 |
|-----------------|-----------------|
| 4-M58-07 = 7ft  | 4-M58-19 = 19ft |
| 4-M58-08 = 8ft  | 4-M58-20 = 20ft |
| 4-M58-09 = 9ft  | 4-M58-21 = 21ft |
| 4-M58-10 = 10ft | 4-M58-22 = 22ft |
| 4-M58-11 = 11ft | 4-M58-23 = 23ft |
| 4-M58-12 = 12ft | 4-M58-24 = 24ft |
| 4-M58-13 = 13ft | 4-M58-25 = 25ft |
| 4-M58-14 = 14ft |                 |
| 4-M58-15 = 15ft |                 |
| 4-M58-16 = 16ft |                 |
| 4-M58-17 = 17ft |                 |
| 4-M58-18 = 18ft |                 |

M58 cables are sold in increments of 1ft from 7ft to 25ft

## Optional Engine Fitting Kits



4-A73 & 4-A74



4-A75

- 4-A73 Tiller Arm for Mercury Engine
- 4-A74 Tiller Arm for OMC, Johnson Evinrude and most other engines
- 4-A75 Clevis