Aquafax







Mechanical steering system for a boat with engines that do not exceed the maximum horsepower rating of the boat

You will need the following:

- 1 x Steering helm
- 1 x Steering cable
- 1 x Steering wheel
- 1 x Engine connection kit (optional)

See also the Aquafax range of Steering System Accessories





Aquafax Limited. 14 Dencora Way, Sundon Business Park, Luton, Beds LU3 3HP

Tel: (01582) 568700 Fax: (01582) 568720

E-mail: sales@aquafax.co.uk Website: www.aquafax.co.uk

4-T85/W Features and Technical Information



- All stainless steel output end of cable as per ABYC P17 safety standards
- · Corrosion resistant materials
- Particularly suitable where clearance is limited
- 90° bezel
- Lock to lock steering wheel turns: approx 3
- Stroke: 230mm (9")
- Minimum steering cable bend radius: 200mm (7.9")
- Exceeds EN 28848 safety standards
- Compact for mounting

4-T85W

Boat Application

- Outboard: Up to 9m (30ft) boat length
- Inboard: Up to 10.5m (35ft) boat length
- Sterndrive: Up to 10.5m (35ft) boat length

For boats that do not exceed 50mph

Steering Wheel


(Max dia 406mm/16")



4-VM24


Various styles of steering wheels are available, please see the full Aquafax range.

M66 Steering Cable



M66 cables are sold in increments of 1ft from 7ft to 40ft

Optional Engine Fitting Kits





- 4-A73 Tiller Arm for Mercury Engine
- 4-A74 Tiller Arm for OMC, Johnson Evinrude and most other engines
- 4-A75 Clevis

FOR GENERAL REFERENCE ONLY

26.05.09