# Aquafax







## Mechanical steering system for a boat with engines that do not exceed the maximum horsepower rating of the boat

You will need the following:

- 1 x Steering helm
- 1 x Mounting bezel kit
- 1 x Steering cable (2 cables reqd for 4-T72FC)
- 1 x Steering wheel
- 1 x Engine connection kit (optional)

See also the Aquafax range of Steering System Accessories





Aquafax Limited. 14 Dencora Way, Sundon Business Park, Luton, Beds LU3 3HP

Tel: (01582) 568700 Fax: (01582) 568720

E-mail: sales@aquafax.co.uk Website: www.aquafax.co.uk

#### 4-T71FC/72FC Features and Technical Information



4-T71FC

- All stainless steel output end of cable as per ABYC P17 safety standards
- Corrosion resistant materials
- Features planetary gear design -

Note: 4-T72FC

Helm requires

2 x M66 Cables

- Particularly suitable where clearance is limited
- Lock to lock steering wheel turns: approx 3.8
- Stroke: 230mm (9")
- Minimum steering cable bend radius: 200mm (7.9")
- Maximum operating load at tiller end: 3300N (340kg: 750lbs)
- Exceeds EN 28848 safety standards

#### **Boat Application**

- Outboard: Up to 9m (30ft) boat length
- Inboard: Up to 10.5m (35ft) boat length
- Sterndrive: Up to 10.5m (35ft) boat length

4-T71FC Helm suitable for boats that do not exceed 50mph

4-T72FC Helm suitable for boats that exceed 50mph

#### **Mounting Bezels**

4-X34 Black 90° Mounting Bezel Kit
4-X34W White 90° Mounting Bezel Kit
4-X35 Black 20° Mounting Bezel Kit





### Steering Wheel

(Max dia 406mm/16")




4-VM24

Various styles of steering wheels are available, please see the full Aquafax range.


#### M66 Steering Cable

4-T72FC



M66 cables are sold in increments of 1ft from 7ft to 40ft

#### **Optional Engine Fitting Kits**





**4-A73** Tiller Arm for Mercury Engine

4-A74 Tiller Arm for OMC, Johnson Evinrude and most other engines

4-A75 Clevis